

Pillar Mechanical Packing

Style No. 6711

- **Braided Packing applicable for high temperature and high-pressure valves**
- **Suitable for steam and oil service High sealability in a single-spool packing**
- **Flexible Graphite Packing with non TTFE used.**



Pillar style No. 6711 is made from a Pillarfoil® yarn with braid over braid construction, reinforced by inconel wire. 6711 is recommended for use in high temperature and high pressure valves.

PILLAR
Engineered Sealing Solutions

GPLC 1222-1

Pillar Mechanical Packing

Style No. 6711



Dimensions

SIZE		LOT Meter/spool (+/-10%)	Spool Size (mm)	Reference		
				ft/spool (+/-10%)	WEIGHT*	
Inches	mm			lbs	kg	
1/8"	3.2	30	φ 130	98.4	1.30	0.6
3/16"	4.8	20		65.6	1.60	0.7
		30	98.4	2.40	1.1	
1/4"	6.4	20	φ 200	65.6	2.90	1.3
5/16"	7.9	10	φ 130	32.8	2.20	1.0
		20		65.6	4.40	2.0
		30	φ 200	98.4	6.60	3.0
3/8"	9.5	20		65.6	6.40	2.9
7/16"	11.1	10	φ 250	32.8	3.80	1.7
		20		65.6	7.60	3.5
1/2"	12.7	10	φ 200	32.8	5.00	2.3
		20	300	65.6	9.90	4.5

* Product weigh (Not include spool & Box)

Specification

pH

0 to 14 (except strong oxidizers)

Temperature

-328 ~ 1100°F (-200 ~ 600°C) *
in steam +840°F (450°C) atmosphere

Pressure

3700psi (259 bar)
ASME class 1500

Application

- 1) Power plant
- 2) Refinery, Petro-chemical
- 3) High Pressure Valve
- 4) Gasket for covers, etc.

Follow the instructions, before installation and operation, for your safety.

* Specifications and dimensions are subject to change without prior notice.

* The data on this catalogue are solely for your reference and are not to be construed as constituting a warranty.

* EDP® and PILLARFOIL® are registered trademark of Nippon Pillar Packing Co., Ltd

NIPPON PILLAR PACKING CO., LTD.

11-48,2-Chome, Nonaka Minami,
Yodogawa-ku, Osaka, 532-0022 Japan
TEL +81 6 6305 2821
FAX +81 6 6302 3300
(URL) <http://www.pillar.co.jp>

DISTRIBUTED BY